

- 1Ω to 100MΩ
- High accuracy
- Clear visual indication
- High stability
- Low temperature coefficient
- Safety terminals
- Removable protective cover
- Suitable for industry or education

DESCRIPTION

A precision wide range resistance decade box designed to meet the requirements of both industry and education. The 1040 is compact and durable, housed in a robust metal case with removable protective rubber cover, making it ideal for use in either the laboratory or field. Excellent accuracy (mid-scale 0.1%) is achieved by using high stability metal film resistors. The 8-digit thumbwheel switch enables simple and precise setting with a clear indication of the resistance value.

Switch Contacts: Special attention has been given to the reliability of operation. A special multiple gold contact arrangement ensures low contact resistance and continued operation even if a contact fails.

Clear Visual Indication: To make selecting and reading the setting easy the 1040 incorporates colour coded digits: megohms - red, kilohms - yellow, ohms - white.

Safety Terminals: Compatible with 4mm shrouded plugs, as well as standard plugs, bare wires, and spade terminals.

Added Protection: The 1040 comes fitted with an ergonomic rubber cover providing increased protection and durability. It has a textured grip for comfortable handling and side openings to place labels. It is easy to remove if the user prefers a stand-alone unit or to house the 1040 in the optional 9026 carry case.

SPECIFICATIONS

Range / Resolution 0 to $100M\Omega$ / 1Ω steps

Decade	1Ω	10Ω	100Ω	1kΩ	10kΩ	100kΩ	1ΜΩ	10ΜΩ
Accuracy	± 1%	± 0.5%	± 0.1%	± 0.1%	± 0.1%	± 0.1%	± 0.1%	± 1%
Max Current	0.5A	0.3A	100mA	30mA	3mA	0.3mA	30μΑ	ЗμА

Voltage Rating Maximum 250V DC/AC RMS

Temperature Coefficient......50ppm/°C

ORDERING INFORMATION

1040	. Wide Range Resistance Decade Box
9026	Leatherette Carry Case
C161	Factory Calibration Certificate (NPL)
C114	. UKAS Calibration Certificate (ISO 17025)

Due to continuous development Time Electronics reserve